



BAHAMAS OIL REFINING COMPANY INTERNATIONAL LTD.

JETTY OPERATING GUIDE LINES - REVISED JANUARY 2012

CRITICAL LIMITATIONS	Dk - 1	12	5	6	7	8	9	10
FENDER SPREAD (FT)	Bulk Hd	140 / 380	235	390	220	250	280	290 / 440
MAXIMUM L.O.A. (FT)	600	750	885	1,200	845	885	960	1, 400
MAXIMUM DWT.								
R.O.C.	43,000	68,000	80,000	264,000	50,000	85,000	120,000	410,000
U.O.C	50,000	80,000	125,000	312,000	65,000	100,000	130,000	500,000
MAX. DISPL. TONS								
R.O.C.	53,000	85,000	98,000	300,000	62,000	107,000	140,000	470,000
U.O.C	63,000	100,000	125,000	360,000	80,000	125,000	150,000	580,000
MAX. NORMAL APPROACH. VELOCITY (FT/SEC)	0.5	0.5	0.3	0.3	0.5	0.5	0.5	0.5
MAX. NORMAL APPROACH. ANGLE (DEGREES)	5	5	6	5	10	10	10	5
MAXIMUM DRAFTS (FT)	28' 6"	44	50 (47)	82	40 (42)	50 (47)	47 (51)	91
NOTES:			(I)	(V)	(II)	(III)	(IV)***	(V)

Notes

R.O.C. - Restricted Operating Conditions. Wave Height 2 - 6ft / Wind Speed less than 30 m.p.h.

U.O.C. - Unrestricted Operating Conditions. Wave Height 0 - 2ft / Wind Speed less than 15 m.p.h.

(I) Arriving / Departing Vessels Heading S.E restricted to 47 ft maximum.

(ii) Departing Vessels Heading N.W. restricted to 42 ft, Departing Vessels heading east restricted to 40 ft draft.

(iii) Arriving / Departing Vessels heading S.E restricted to 47ft maximum draft. Pilots may be able to bring vessels in from the N.W stern first, conditions permitting.

(iv) Arriving vessels maximum draft 47ft, Departing vessels heading East maximum draft is 51ft.

(v) Maximum freeboard is 65ft.

(VI) Minimum Parallel Body Length for all ships at Berth 6 should be no less then 420 feet.

(VII) Minimum Parallel Body Length for ships with center manifold at Berth 12 should be no less then 160 feet.
For other ships the parallel body length forward and AFT of the manifold should be no less than 80 feet.